

VP 2440/3040/3640/2400/3000/3600/HD

Overview

The **VacPack VP Series** are premium impulse vacuum gas flush sealers with advanced features and specifications for the most demanding modified atmosphere packaging. The VP Series includes tabletop, floor stand and heavy duty sealers. The premium VP Series comes standard with washdown IP 65 capabilities, wider seal lengths than the VS Series, dual upper and lower sealing bars, enhanced controls, and advanced filtration on all models. The VP Series produces hermetically sealed packages on any heat sealable bag up to 12 mil/300 micron thick (6 mil/150 micron when gusseted).

The easy-to-use programmable color touchscreen interface provides integrated recipe management, user-defined preferences for fast, repeatable set up, advanced control and monitoring of all key vacuum gas flush and sealing processes. Numerous options and upgrades allow users to customize the VP Series to your unique product demands and packaging environment.

The **VP 2440, 3040, and VP 3640** comes in a compact tabletop design.

Features & Benefits

- Multi-stage vacuum, gas flush
- Dual upper and lower sealing bars
- Extra-wide seal lengths
- Plug and play
- Low maintenance
- Easy-to-clean IP 65 capabilities
- NEMA 4 cover for HMI (VP HD)
- Heavy duty air cylinders
- Powerful easy-to-use 5.7" color touchscreen
- Fast, simple changeovers
- Advanced filtration (Stage 3 kit VP HD)
- Low pressure safety close
- Bag Clips (VP HD)
- Multilingual programming
- Recipe management
- User-defined preferences for fast, repeatable set up
- Numerous options and upgrades

Specifications

Electrical: 120V 12 A or 220V 6A

Sealer Duty: Impulse

Multi-Stage Vacuum/Gas Flush: 2 ejector style, stainless steel nozzles

Air Requirement: 15 CFM 80 PSI (VP 2440/3040/3640/2400/3000/3600) 90 PSI, 26.4 ELM (VP HD)

Orientation: Horizontal tabletop (VP 2440/3040/3640). Vertical floor stand (VP2400/3000/3600/HD)

Sealer Bar: Anodized Aluminium; Top and bottom seal bars

Sealing Width: 1/4" (6.35 mm) (VP 2440/3040/3640/2400/3000/3600) Choice of: 1/4" (6.35 mm), 1/8" (3 mm), 3/8" (9mm) (VP HD)

Usable Seal Length: 24" (60.9 cm), 30" (76.20 cm), or 36" (91.4 cm)

Seal Throat Depth: 5" (12.7 cm)

Pressure Control: Manual (VP 2440/3040/3640). Digital (VP 2400/3000/3600/HD)

Time Control: Digital

Frame: 316L Stainless Steel

Environmental Protection: Standard Cleaning and Wipedown



The **VP 2400, 3000, and VP 3600** come with a 316L stainless steel adjustable stand with vertical or angled bag sealing for increased flexibility and versatility.

The **VP HD** includes the standard VP features plus large diameter tubing and heavy-duty fittings, extended 8" nozzles, a stage 3 filter kit, washdown cover for HMI controls, shut-off valve for nozzles, and bag clips. The VP HD is an ideal solution for bag in box and bulk applications.

Maintenance: One touch removal of vacuum gas flush tubes, easy change nichrome and Teflon cover, and maintenance alerts

Controller: Programmable 5.7" color touchscreen

Options

- Additional Nozzles
- Extended Seal Lengths
- NEMA 4 or NEMA 4X
- Validatable Sealing
- Product Shelf

Videos & Web Content

