

MP-2/MP-3



Overview

The MP Series is a highly efficient complete shrink system that includes an integrated L Bar Sealer and Shrink Tunnel on a compact frame.

MP Combo Systems produce attractive packages for a wide range of stable and unstable products. All Combo Systems provide quick changeover and easy film load, intuitive controls and precise seal and wrapping adjustments for strong, accurate shrink wrapping. Frames are available in heavy duty painted steel or stainless steel for durable, long lasting performance. Combo Systems include the same precise controls and adjustments for speed, temperature, and wrapping as our industry leading stand alone L-Bar sealers.

MP Combo Systems are available in two main configurations—the MP-2 and the MP-3.

The MP-3 adds a variable speed discharge conveyor to the standard MP-2 model.



MP-2

Numerous options and upgrades allow users to customize the MP Series to their unique product demands.

Features & Benefits

- Counterbalanced sealing head with automatic air cushion return
- Electromagnetic seal bar hold down
- Electronic control system for sealer and shrink tunnel
- Adjustable stainless steel loading platform
- Variable speed Teflon mesh belt conveyor
- Quick change film system—easily adjustable for different sized rolls.
- Film clamps
- Perforator roller for air evacuation from completed package
- Locking casters
- Top, side and bottom heat vents
- Variable speed discharge conveyor (MP-3)

Specifications

Seal Head Width: 14" (35.56 cm)

Seal Head Length: 18" (45.72 cm)

Height at Center: 4" (10.16 cm)

Max Film Width: 18" (45.72 cm)

Construction: Aluminium & Stainless Steel or Painted Steel

Machine Stand: Choice of Stainless Steel Locking Casters or Footpad

Product Loading: Adjustable Stainless Steel Platform

Speed: Operator/application dependent

Infeed: Right to left

Film Rollers: Adjustable Film Cradle and Perforator Roller

Film Roll Storage Shelf

Film Changeover: Quick Change Film System

Discharge Conveyor: Variable Speed (MP-3)

Power Requirement 220 V 6A

Cleaning: Standard Cleaning and wipedown

Options

- Hot Knife
- Power Film Unwind with Adjustable Inverting Head
- Teflon Blinds for LDPE
- Right to Left Infeed Orientation

Videos & Web Content

